

ProDyne

Product & Mixing Guide

PRIMARY BENEFITS

- Softens hard water for polymers, leading to faster hydration
- Non-foaming
- Keeps drill bit clean of debris by reducing the “stickiness” of clay materials and cuttings
- Can be used in conjunction with ProAction’s ProBore or ProVis Series, along with other brands of bentonite

FAQ's

Do I always need to use ProDyne when running ProDrill?

No, ProDyne is necessary when low density, sticky soil material that wants to cling to rods and tooling are present, and in projects that might have been “water only” traditionally, can be a great low cost additive to increase productivity and efficiency. ProDyne is compatible with all ProAction products so it can be run as needed with any ProAction mud mix—ProBore or ProVis.

Can ProDyne be used to create a foam?

No, ProDyne is non-foaming. Contact your local distributor for information on ProAction Fluids’ ProFoam product.

Will ProDyne freeze?

ProDyne will turn to slush at temperatures below 20°F (-7°C). This does not affect the performance, and it will fully activate when introduced into a fluid system.

ProDyne™ is a water based, water soluble non-foaming drilling detergent builder and water conditioner/chelator. The water-based formulation makes it easily dispersible in water, with little mixing energy required. ProDyne acts as a water conditioner in hard or mineral-laden water, and water wets downhole equipment such as rods and tooling, ultimately contributing to longer tooling and rod life, lower drilling temperatures.

MIXING GUIDE

► 1 EZB (Bag or Bottle) treats 500 gallons

ProDyne is a great supplemental additive for any soil condition, even sand or rock. The ability to keep tooling clean leads to more efficient drilling by keeping cutting surfaces exposed, tooling cool, and rods free of organic material that would have a negative effect on rotational torque. Use it to achieve full hydration of ProAction polymer products such as ProDrill or GeoSweep HD.

ProAction recommends ProDyne™ be the first additive into any fluid system. In order to receive the full water softening benefit, ProDyne™ must be added and mixed before any polymer.

Does your soil have sticky clay, silt and/or hard water?

add **ProDyne**

	Water	1/2 EZB
LOW (Density, Permeability, & Grain Size)	<i>Sticky Clay</i>	1 EZB
SOIL	<i>Swelling Clay</i>	
	<i>Mixed Sand</i>	
	<i>Fine Sand</i>	
	<i>Medium Sand</i>	
	<i>Coarse Sand</i>	
	<i>Pea Gravel</i>	
HIGH ROCK	<i>Pebbles</i>	
	<i>Cobble Rocks</i>	

