



Scan for Product Information

**OVERVIEW:**

HammerLube is specifically formulated to provide outstanding protection for percussion drills and rock hammers. Premium base stocks combined with highly effective additive technology provide the best anti-wear and shock protection. Tackifying agents and corrosion inhibitors resist wash-out and fling-off, maintaining lubrication and protection against rust and corrosion.

**APPLICATIONS & BENEFITS**

HammerLube is an excellent lubricant choice for any air-impact or percussive heavy-duty tool. This formula provides multiple benefits including:

- Reduced wear and deterioration at hammer impact faces
- Increased protection against rust and corrosion
- Improves operation and extends equipment life

**TYPICAL PROPERTIES:**

Property	Test Method	
ISO Viscosity Grade	ASTM D2422	100
AGMA Viscosity Grade	AGMA 9005-D94	3
Viscosity	ASTM D445	cSt. @ 40 °C
		cSt. @ 100 °C
Viscosity Index	ASTM D2270	104
Specific Gravity @ 60 °F (15 °C)	ASTM D4052	0.876
Flash Point, °F (°C)	ASTM D92	400 (204)
Pour Point, °F (°C)	ASTM D97	10 (-12)
Tackifier		Yes

**PACKAGING:**

HammerLube is packaged into 5-gallon pails.